

Description

The D1430 Hybrid® OxyProbe® amperometric dissolved oxygen (DO) sensor is designed for installation into SU100 series gas wells.

Purchase Information

Part Number	D1430-120-V8
Description	DO sensor for SU100 series gas wells

Classification

Model Type	D1430
Product Type	DO Sensor

Specifications

Measurement

Type	Dissolved Oxygen
Principle	Amperometric
Range	0–500 nA [0–300% SAT]
Drift	≤ 0.1% SAT per day

Operational Range

Temperature	5°–50° C [41°–122° F]
Pressure	0–3750 mmHg [0–72 psig]
Flow Rate	Not applicable

Signal

Input	675 mV Polarization Voltage (from transmitter)
Output	Analog: nAmps Metadata: Digital: SensorTalk®

Sterilization

Autoclavable	Not autoclavable
Steam Sterilizable	Not steam sterilizable
Gamma Sterilizable	Not gamma sterilizable

Connectors and Cables

Connector	8-pin Variopin Disconnect Cap
Cable Length	Not applicable

Process Interface

Insertion Method	Pg13.5 Threaded Retainer Fitting
Insertion Length	120 mm [4.75 inches]

Wetted Materials

Not applicable



Hybrid® OxyProbe® DO Sensor

Packaging and Regulations

Packaging Information

Package Type	Cardboard box
Package Dimensions	20.32 x 10.16 x 5.72 cm [8 in x 4 in x 2.25 in]
Package Weight	< 0.5 kg [1 lb]
Double Bagged	No
Cleanroom Bagged	No
Cleanroom Class.....	Not applicable
Storage Conditions.....	Temperature: 5°–35° C [41°–95° F] Humidity: 5–95 RH
Included Accessories	Not applicable
Quality Certificate	Included
Shelf Life	60 months
Shelf Life Post Gamma Sterilization	Not applicable

Origination and Tariff Code

Harmonized Tariff Trade Code.....	9027803100
Country of Origin	USA
MFR Location	California, USA

Purchasing Information

Unit of Sale.....	Each
Minimum Purchase Quantity	Each

Regulatory and Compliance

CE Compliant	Yes
RoHS Compliant	Yes
REACH Compliant	Yes
CFR 21-11 Compliant	Not applicable
BSE/TSE/ADI Compliant.....	Yes
USP Class VI Compliant	Yes
FDA Material Compliant	Yes

The contents of this publication are presented for information purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding products or services described herein or in their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the design or specification of such products at any time.



North America and Pacific

Email: sales@broadleyjames.com
Web: www.broadleyjames.com

Phone: 949-829-5555
Toll-free: 800-288-2833
Fax: 949-829-5560

19 Thomas, Irvine, CA, 92618 USA

United Kingdom and EU Countries

Email: sales@broadleyjames.co.uk
Web: www.broadleyjames.eu

Phone: +44 (0)1525 862518
Fax: +44 (0)1525 862811

Wrest Park, Silsoe, Bedford MK45 4HS, UK