

Single-Use, Flow-Through pH Sensor
with 1/8-inch Hose Barbs

Description

The SU600-02 SingleSense® Single-Use pH Sensor is a flow-through sensor with 1/8-inch hose barbs. Designed for downstream bioprocess applications.

Purchase Information

Part Number	SU600-02
Description	Single-use flow-through pH sensor, 1/8-inch

Classification

Model Type	SU600
Product Type	pH Sensor

Specifications

Measurement

Type	pH
Principle	Potentiometric
Range	2–12 pH
Drift	≤ 0.01 pH per day

Operational Range

Temperature	15°–50° C [60°–122° F]
Pressure	0–3040 mmHg [0–45 psig]
Maximum Flow Rate	0.9 liters/minute [0.23 gallons/minute]

Signal

Input	Not applicable
Output	Sensor: Millivolts: ± 414

Sterilization

Autoclavable	Not autoclavable
Steam Sterilizable	Not steam sterilizable
Gamma Sterilizable	Yes, up to 50 kGy

Connectors and Cables

Connector	8-pin Variopin
Cable Length	0.15 m [6 inches]

Process Interface


Insertion Method	1/8-inch Hose Barbs
Insertion Length	Not applicable

Wetted Materials


PEEK, USP Class VI, ADI-Free, Extraction Tested
Dimethyl Silicone Rubber, Pt Cure, USP Class VI Extraction Tested, 21CFR, 177.2600
EPDM USP Class VI, FDA Compliant, ADI-Free
HDPE, USP Class VI
Lead-Free Glass, Alumina Silicate



Isometric View



Side View



Top View with Dial Face



Packaging and Regulations

Packaging Information

Package Type Cardboard box with double-bagged sensor inside

Package Dimensions 30.48 x 30.48 x 5.08 cm [12 in x 12 in x 2 in]

Package Weight < 0.5 kg [1 lb]

Double Bagged Yes, sensor is double-bagged

Cleanhood Bagged Yes, inner bag only

Cleanhood Class Class 7 Clean Air Hood

Storage Conditions Temperature: 5°–35° C [41°–95° F]

Included Accessories Not applicable

Quality Certificate Included

Shelf Life 36 months

Shelf Life Post Gamma Sterilization 30 months

Origination and Tariff Code

Harmonized Tariff Trade Code 9027803100

Country of Origin USA

MFR Location California, USA

Purchasing Information

Unit of Sale Each

Minimum Purchase Quantity Each

Regulatory and Compliance

CE Compliant Yes

RoHS Compliant Yes

REACH Compliant Yes

CFR 21-11 Compliant Not applicable

BSE/TSE/ADI Free Yes

USP Class VI Compliant Yes, all wetted parts

FDA Material Compliant Yes, all wetted parts

The contents of this publication are presented for information purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding products or services described herein or in their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the design or specification of such products at any time.

Doc Nbr: PDS-112055 R5

Published 24 April 2024

© April 2024 Broadley-James Corporation. All rights reserved. Visit www.broadley-james.com/IP for trademark and patent information.

TMP-PDS-112001 R1